

IP54

CAM INDEXERS
 GC50, GC80, GC95, GC110, GC140, GC150, GC180, GC200, GC250
 RT85, RT100, RT150, RT240
 HD190, HD265, HD315
 PC40, PC50, PC63, PC80, PC100, PC125, PC160, PC200, PC250

IP Rating Chart

IP ratings are represented by combining the first and second digits of the following columns. See example below.

1st Digit - SOLID

Degree of protection against solid objects



No Protection **0**



Protected against a solid object greater than 50mm, such as a hand. **1**



Protected against a solid object greater than 12.5mm, such as a finger. **2**



Protected against a solid object greater than 2.5mm, such as a wire. **3**



Protected against a solid object greater than 1.0mm, such as a thin strap. **4**



Dust Protected. Prevents ingress of dust sufficient to cause harm. **5**



Dust tight. No ingress of dust. **6**

2nd Digit - LIQUID

Degree of protection against water



No Protection **0**



Protected against water drops. **1**



Protected against water drops at a 15 degree angle. **2**



Protected against water spray at 60 degree angle. **3**



Protected against water splashing from any angle. **4**



Protected against water jets from any angle. **5**



Protected against powerful water jets and heavy seas. **6**




Protected against the effects of temporary submersion in water. (30 minutes at 3 feet) **7**



Protected against the effects of permanent submersion in water. (Up to 13 feet) **8**

Example:



For additional technical information, contact Packam:
info@packam.co.in